



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## Quick Dry®

MSDS Number: BLM007

Revision Date: 5/18/2015

Page 1 of 6

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer

PROFILE Products, LLC  
750 LAKE COOK ROAD  
SUITE 440  
BUFFALO GROVE, IL 60089

**Phone:** (847) 215-1144  
**Fax:** (847) 215-0577  
**Web:** www.profileproducts.com

**Product Name:** Quick Dry®  
**Revision Date:** 5/18/2015  
**MSDS Number:** BLM007  
**Common Name:** N.A.  
**CAS Number:** 70892-59-0

Description: Heat Treated Montmorillonite Clay Mineral.

### 2 HAZARDS IDENTIFICATION

**Inhalation:** Lungs  
**Skin Contact:** Wash with soap and water until clean.  
**Eye Contact:** Wash out with water.  
**Ingestion:** No adverse effect.

NFPA: Health = 1, Fire = 0, Reactivity = 0



## Quick Dry®

MSDS Number: BLM007

Revision Date: 5/18/2015

Page 2 of 6

GHS Signal Word:  
WARNING

GHS Hazard Pictograms:



GHS Classifications:  
Health, Specific target organ toxicity - Single exposure, 3

GHS Phrases:  
H335 - May cause respiratory irritation

GHS Precautionary Statements:  
P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Crystalline Silica (Quartz) [EPA Hazard Category: Health]

Carcinogen: OSHA - No NTP - Yes (respirable) IARC - Yes

This product contains up to 5% crystalline silica. The International Agency for Research on Cancer (IARC) has stated that there is sufficient evidence of carcinogenicity of crystalline silica to human beings. It was noted that carcinogenicity was not detected in all industrial circumstances studied. The NTP's Sixth Annual Report on Carcinogens include respirable crystalline silica. The Hazard Communication Standard (29CFR 1910.1200) requires that any material containing over 0.1% of a substance reported as a carcinogen in an IARC monograph or the most recent NTP Annual Report on Carcinogens must be identified as a carcinogen. These identifications are for hazard communications only and do not serve as assessments of carcinogenic risk. Crystalline silica is known to cause silicosis. At dust levels below the recommended PEL exposure to the crystalline silica contained in this product should not present a health hazard.

Inhalation of excessive concentrations of any dust, including this material, may lead to lung injury. As formulated, this product is not expected to form appreciable respirable crystalline silica dust from use or attrition. Because application and exposure data indicate exposure to respirable quartz in the normal use of the ingredient within this product which contains crystalline silica, is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV). Adverse effects would not be expected from normal use of this product

3	<b>COMPOSITION/INFORMATION ON INGREDIENTS</b>
---	---

**Ingredients:**

Cas #	Perc.	Chemical Name
14808607	3-5%	Silica, crystalline quartz



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## Quick Dry®

MSDS Number: BLM007

Revision Date: 5/18/2015

Page 3 of 6

4

### FIRST AID MEASURES

**Inhalation:** Move to fresh air.  
**Skin Contact:** Wash thoroughly with soap and water.  
**Eye Contact:** Flush thoroughly with water. See a physician if discomfort persists.  
**Ingestion:** None. If large quantities are ingested consult your physician.

5

### FIRE FIGHTING MEASURES

Non-flammable and non-hazardous

6

### ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.

7

### HANDLING AND STORAGE

**Handling Precautions:** Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.  
**Storage Requirements:** Store in dry area.



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## Quick Dry®

MSDS Number: BLM007

Revision Date: 5/18/2015

Page 4 of 6

8	<b>EXPOSURE CONTROLS/PERSONAL PROTECTION</b>
---	--

**Personal Protective Equip:** Respiratory Protection: If dust concentrations exceed recommended Permissible Exposure Limits, use NIOSH- approved dust respirators, with approval TC-21C-xxx, until feasible engineering controls are completed.  
Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than Permissible Exposure Limits is recommended.  
Eye Protection: If high dust concentrations exist, tight-fitting goggles are recommended to reduce dust exposure to the eyes.  
Other Protective Equipment: Optional.

Exposure Limits (respirable fraction) in Air:  
OSHA & MSHA - PEL 10mg/m3  
% SiO2 + 2 (8-Hour TWA)  
ACGIH - TLV 0.05 mg/cubic meter (8-Hour TWA)  
NIOSH 0.05mg/cubic meter (10-Hour TWA, 40-hour work week)

Exposure Limits refer to the respirable fraction.  
PEL means OSHA Permissible Exposure Limit.  
TLV means American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value.  
MSHA means Mine Safety and Health Administration Exposure Limit.  
TWA means 8 hour Time Weighted Average.

9	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
---	---

<b>Appearance:</b>	Brown to buff-colored granular particles	<b>Odor:</b>	Negligible
<b>Physical State:</b>	Solid granular particles	<b>Solubility:</b>	Negligible
		<b>Freezing/Melting Pt.:</b>	N.A.
		<b>Bulk Density:</b>	38 lbs/cubic ft.

10	<b>STABILITY AND REACTIVITY</b>
----	---------------------------------

**Stability:** Quick Dry is stable under all normal conditions.  
**Materials to Avoid:** Unreacted polymer monomers  
**Hazardous Decomposition:** None Known  
**Hazardous Polymerization:** Will not occur.

11	<b>TOXICOLOGICAL INFORMATION</b>
----	----------------------------------

Inhalation- N.E.  
Intravenous- Rat - LD50:15mg/kg  
Oral - Rat - LD50:3160 mg/kg



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## Quick Dry®

MSDS Number: BLM007

Revision Date: 5/18/2015

Page 5 of 6

12	<b>ECOLOGICAL INFORMATION</b>
----	-------------------------------

Natural occurring mineral - None Determined

13	<b>DISPOSAL CONSIDERATIONS</b>
----	--------------------------------

Can be disposed of in an approved disposal facility, in accordance with applicable federal, state, and local regulations. The nature and extent of contamination, if any, may require use of specialized disposal methods.

14	<b>TRANSPORT INFORMATION</b>
----	------------------------------

DOT Class: Not regulated #

Ground Clay contains crystalline silica in solid form

WHMIS Classification D2A

WHMIS Label on each package

Not TDG regulated

15	<b>REGULATORY INFORMATION</b>
----	-------------------------------

COMPONENT / (CAS/PERC) / CODES

-----  
\*silica, crystalline quartz (14808607 3-5%) MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS

-----  
MASS = MA Massachusetts Hazardous Substances List

NRC = Nationally Recognized Carcinogens

OSHA = OSHA workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TXAIR = TX Air Contaminants with Health Effects Screening Level

TSCA = Toxic Substances Control Act



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## Quick Dry®

MSDS Number: BLM007

Revision Date: 5/18/2015

Page 6 of 6

16

### OTHER INFORMATION

**Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).